



帝驰科技

广州帝驰科技有限公司

GUANGZHOU KINGWINGS TECHNOLOGY CO., LTD

E-mail: info@chinakwings.com Tel: 0080-20-3156 3639

2K Filler Introduction

Two component acrylic filler applied before the application of 2k acrylic paints or solvent based basecoats in order to obtain maximum filling and superior finish.	PRODUCT
<ul style="list-style-type: none">• Maximum Filling• Excellent adhesion• Easy sanding	FEATURES
Car repair, Industrial coating, Bare steel and properly prepared old finishes.	RECOMMENDED USE
<p>Finish : Matt</p> <p>Viscosity : 90 ± 5 Kerbs unit @ 30°C</p> <p>Colour : Grey, White & Black</p> <p>Density : 1.6 ± 0.1 gram/cm³</p> <p>Mixing ratio : Base :Hardener = 4:1</p> <p>Pot Life : 4 hrs</p> <p>Drying time @ 20°C : 3.5-4 hrs</p> <p>Sandpaper : P320 followed by P600</p> <p>Pack size : 1 Litre</p> <p>Pressure : 2-3 bar</p> <p>Nozzle dia : 1.8-2mm</p>	SPECIFICATION & OTHER INFORMATION

<ul style="list-style-type: none"> • Surface should be clean from all dust, rust, wax, oil, grease, loose particles, flakes and other contaminants. • 2k Filler can be applied over Polyester putty, epoxy primer. • Remove dust from the surface. • Substrate temperature min: 8°C, max: 35°C • Surface to be recoat should be cleaned thoroughly before application. 	SURFACE PREPARATION & APPLICATION
---	--

<p>Storage & Disposal : Store in cool, dry condition. & dispose by controlled land fill as per requirement of statutory authority. Don't empty into drains, sewers or other water courses. Never keep the lid of hardener pack open.</p> <p>Shelf Life : Up to 1 year under sealed condition.</p>	STORAGE & HANDLING
---	-----------------------------------

<ul style="list-style-type: none"> ▪ Avoid contact with the skin and eyes. Wear suitable protective clothings such as overalls, goggles, dust mask and gloves. Use a barrier cream. ▪ Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. ▪ This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon-dioxide or dry chemicals. ▪ Eyes & Skin: In the event of accidental splashes, flush eyes with warm water & wash skin with mild soap and seek quick medical advice. Never use solvent for cleaning the affected areas. ▪ Inhalation & Ingestion: Remove to fresh air, loosen collar. Don't induce vomiting. 	SAFETY PRECAUTIONS & FIRST AID
--	---

<p>The product information sheet is meant for general information of the product. Optimal performance by the product would be achieved on correct selection of paint & painting system, proper surface preparation & application. Unless specifically agreed in writing by us we won't be responsible for 100% performance of the product. Product information sheet would be subject to modification as & when product is modified/improved. Our endeavor would be to keep you abreast of change.</p>	DISCLAIMER
--	-------------------