










帝驰科技

广州帝驰科技有限公司
GUANGZHOU KINGWINGS TECHNOLOGY CO., LTD

Automotive Refinish Paint Series Plastic Primer

Characteristic Features: 1K fast dry plastic primer, easy to apply

Substrates: Dried and Sanded existing finish, PP, PE, PVC, Rubber, Acrylic Board

	Surface Cleaning: Remove waxing, silicon, dust, rust with degreaser								
	<table border="1" data-bbox="619 696 1235 819"> <tr> <td data-bbox="619 696 799 757">Mixing Ratio (Volume)</td> <td data-bbox="799 696 1018 757">Plastic Primer</td> <td data-bbox="1018 696 1235 757" rowspan="2" style="text-align: center;">/</td> <td data-bbox="1018 757 1235 819">Thinner</td> </tr> <tr> <td data-bbox="619 757 799 819"></td> <td data-bbox="799 757 1018 819" style="text-align: center;">1</td> <td data-bbox="1018 757 1235 819" style="text-align: center;">1</td> </tr> </table>		Mixing Ratio (Volume)	Plastic Primer	/	Thinner		1	1
Mixing Ratio (Volume)	Plastic Primer	/	Thinner						
	1		1						
	Spray Gun Setting	Gravity Feed: 1.4-1.7mm,3-5kg/cm ²							
		Siphon Feed: 1.5-1.8mm 3-5kg/cm ²							
	Coats & Thickness	1-2 coats, 5-10um							
	Flash-off Time	5-10 minutes at 25 °C							
	Pot Life	At 25°C in 30 Minutes							
Shelf Life	2 Years in original sealed packaging at Cool, Dry,Well ventilation store room at 25°C								
Packaging	1L*12 Cans/CTN, 5L*4 Cans/CTN								